



Вспомогательный контакт 2НО+2НЗ

Тип +IZM-AS22
Каталог № 122758

Программа поставок

Принадлежности			Вспомогательные контакты
Принадлежности			Стандартный вспомогательный контакт для сигнализации включения/выключения
			2 размыкающих и 2 замыкающих контакта дополнительно
Применяемое для			IZM20, 32, 40, 63... IN20, 32, 40, 63...

Технические характеристики

Расчетная разрывная способность

Индуктивная нагрузка			
250 В переменного тока		A	10
125 В пост. тока		A	0.5
250 В пост. тока		A	0.25

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Мин. рабочая температура		°C	-25
Макс. рабочая температура		°C	70

Технические характеристики согласно ETIM 4.0

Number of contacts as change-over contact			0
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			2
Suitable for panel push button			No
Suitable for earth leakage switch			No
Suitable for front element			No
Suitable for hanging switch			No
Suitable for pendant control station			No
Suitable for auxiliary relay			No
Suitable for impulse relay			No
Suitable for installation protection/installation relay			No
Suitable for earth leakage circuit breaker			No
Suitable for switch disconnecter kompakt			No
Suitable for power circuit breaker			Yes
Suitable for power protection			No
Suitable for miniature circuit breaker			No
Suitable for over current-/earth leakage switch			No
Suitable for magnetic switch			No
Suitable for motor safety switch			No
Suitable for cam-type control switch			No
Suitable for position switch			No
Suitable for modular relay			No
Suitable for safety position switch			No
Suitable for current surge switch			No
Suitable for level switch			No
Rated operation current Ie at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Mounting method			Half-integrated

