




Hollow wall wall trough 3-row; form of delivery for projects

**Part no.** KLV-HW3-4PR  
**Catalog No.** 178844

## Delivery program

|  |       |  |   |
|--|-------|--|---|
| Product image                                    |       |  |             |
| Basic function                                   |       |  | Basic device  |
| Product function                                 |       |  | Installation distribution boards  |
| Product range                                    |       |  | KLV for projects  |
| Design   |       |  | Hollow wall   |
| Installation site                                |       |  | Indoor  |
| Type of installation                             |       |  | Hollow-wall mounting  |
| Door/Flap  |       |  | White   |
| Degree of Protection                             |       |  | IP30  |
| Colour   |       |  | White   |
| Shroud for protection against accidental contact |       |  | Plastic   |
| Rows   | Count |  | 3   |
| Module units per row                             |       |  | 12  |
| Description                                      |       |  | IP30<br>Protection Class II<br>Plastic housing  |
| Cable entries                                    |       |  | Cable entries on top and bottom, side, back plate   |
| Equipment supplied                               |       |  | Empty wall trough<br>Spirit level<br>Hollow-wall anchor<br>Guard<br>Installation instructions |

## Technical data

### General

|   |    |      |                                    |
|---|----|------|------------------------------------|
| Standards   |    |      | IEC/EN 62208, IEC/EN 60670-24 (PD) |
| RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council) |    |      | conform                            |
| Ambient temperature   |    | °C   | -5 - +40                           |
| Degree of Protection  |    |      | IP30                               |
| Protection class  |    |      | II (totally insulated)             |
| Rated operational voltage   | Ue | V AC | 400                                |
| Rated frequency   | f  | Hz   | 50                                 |

### Material characteristics

|          |  |  |                      |
|----------|--|--|----------------------|
| Material |  |  | Polystyren (plastic) |
| Colour   |  |  | white (RAL 9016)     |

### Material properties

|                   |  |  |      |
|-------------------|--|--|------|
| Mechanical        |  |  |      |
| Impact resistance |  |  | IK05 |

## Technical data ETIM 7.0

|  |  |  |       |
|--|--|--|-------|
| Distribution boards (EG000023) / Accessories for small distribution board (EC002287)   |  |  |       |
| Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Electrical distribution system (incl. small distribution board, accessories) (ec@ss10.0.1-27-14-24-92 [AFR782003]) |  |  |       |
| Type of accessory  |  |  | Other |

## Additional product information (links)

Product overview (Web)

<http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm>