



Предохранитель, среднее напряжение, 40 А, AC 5.5 kV, 50 кА, 76 x 403 мм, полный диапазон, ANSI, с наклейкой, тип E, 40E

Тип **5.5KV 40Amp 3" FULL RANGE FUSE**
Каталог № **5.5FFNHA40E**

Abbildung ähnlich

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Область применения			среднее напряжение
Номинальный ток	I	A	40
Номинальное напряжение			AC 5.5 kV
Типоразмер			76 x 403 mm
Категория применения			полный диапазон
Индикатор состояния			с наклейкой
Описание			тип E
Отключающая способность		кА	50
возможно использование для типоразмеров/оборудования			защита первичной обмотки трансформатора защита питающей линии
Характеристика размыкания	Класс		40E
Стандарт/сертификат			ANSI
Форма			цилиндрический
Стандарты/предписания			ANSI C37-42

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	40
Rated voltage		kV	5.5
Voltage type			AC
Rated frequency		Hz	60 - 60
Breaking capacity		kA	50
Utilization category			Other
Application			Primary side transformer protection
Length		mm	403
Diameter		mm	76
Performance category according to IEC 60282-1			Full-range
With striker			Yes
Standard			ANSI
Release characteristic			E
Installation technique			Air