



Воздушный предохранитель, среднее напряжение, 6.3 А, AC 3.6 kV, 51 x 359 mm, резерв, BS, с наклейкой



Тип **3.6KV 6.3Amp 2" 'A' Air Fuse ADG**  
 Каталог № **3.6ADGHA6.3**

Abbildung ähnlich

### Программа поставок

|  |   |   |  |
|--|---|---|--|
| Программа поставок                                   |   |   | Предохранитель                           |
| Основная функция                                     |   |   | Воздушный предохранитель                 |
| Область применения                                   |   |   | среднее напряжение                       |
| Номинальный ток                                      | I | A | 6.3                                      |
| Номинальное напряжение                               |   |   | AC 3.6 kV                                |
| Типоразмер   |   |   | 51 x 359 mm                              |
| Категория применения                                 |   |   | резерв                                   |
| Индикатор состояния                                  |   |   | с наклейкой                              |
| возможно использование для типоразмеров/оборудования |   |   | защита первичной обмотки трансформаторов |
| Стандарт/сертификат                                  |   |   | BS                                       |
| Форма  |   |   | цилиндрический                           |
| Стандарты/предписания                                |   |   | BS2692-1                                 |

### Технические характеристики согласно ETIM 7.0

|  |  |    |                                     |
|--|--|----|-------------------------------------|
| Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) |  |    |                                     |
| Rated current  |  | A  | 6.3                                 |
| Rated voltage  |  | kV | 3.6                                 |
| Voltage type   |  |    | AC                                  |
| Rated frequency  |  | Hz | 50 - 50                             |
| Breaking capacity  |  | kA | 25                                  |
| Utilization category   |  |    | Other                               |
| Application  |  |    | Primary side transformer protection |
| Length   |  | mm | 359                                 |
| Diameter   |  | mm | 51                                  |
| Performance category according to IEC 60282-1                                |  |    | Back-up                             |
| With striker   |  |    | Yes                                 |
| Standard   |  |    | British Standard                    |
| Release characteristic   |  |    | Other                               |
| Installation technique   |  |    | Air                                 |