



Соединительная шина, 2 фазы, 4 модуля

Тип **EVG-16/2PHAS/4MODUL/HI**
Каталог № **291482**

Abbildung ähnlich

Программа поставок

Основная функция		Сборная шина
Основная функция дополнительного оснащения		Сборная шина для линейного защитного автомата Сборная шина для дифференциальной защиты Сборная шина для переключателя комбинированной защиты FI/LS
Тип сборной шины		двухфазный + HS
Ассортимент		EVG

Технические характеристики согласно ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Электротехника, электроника, системы автоматизации / Низковольтная коммутационная техника / Component for low-voltage switching technology / Phase busbar (ecI@ss10.0.1-27-37-13-06 [ACN992011])		
Number of phases		2
Number of poles		2
Suitable for number of devices		2
Pitch dimensions	mm	0
Cross section	mm ²	16
Length	mm	178
Number of modular spacings		4
Rated permanent current Iu	A	80
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current Iq	kA	25
Max. rated operation voltage Ue	V	415
Rated short-time withstand current Icw	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		Yes

Размеры

