



**Предохранитель, среднее напряжение, 150 А, AC 8.25 kV, 50 кА, 76 x 254 мм, полный диапазон, ANSI, тип E, Специальный наконечник, 150E**

**Тип** 8.25KV 150E RATING TWIN  
**Каталог №** 8.25FFNHK150E

Abbildung ähnlich

## Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Область применения			среднее напряжение
Номинальный ток	I	A	150
Номинальное напряжение			AC 8.25 kV
Типоразмер			76 x 254 mm
Категория применения			полный диапазон
Описание			тип E Специальный наконечник
Отключающая способность		кА	50
возможно использование для типоразмеров/оборудования			защита первичной обмотки трансформаторов
Характеристика размыкания	Класс		150E
Стандарт/сертификат			ANSI
Форма			цилиндрический
Стандарты/предписания			BS2692-1

## Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	150
Rated voltage		kV	8.25
Voltage type			AC
Rated frequency		Hz	60 - 60
Breaking capacity		kA	50
Utilization category			Other
Application			Primary side transformer protection
Length		mm	254
Diameter		mm	76
Performance category according to IEC 60282-1			Full-range
With striker			Yes
Standard			ANSI
Release characteristic			E
Installation technique			Air