



**Модульная кнопка ЗНО**

**Тип** Z-S/3S  
**Каталог №** 248334

**Bauartnachweis nach IEC/EN 61439**

Технические характеристики для подтверждения типа конструкции			
Номинальный ток для указания потери мощности	$I_n$	A	20

**Технические характеристики согласно ETIM 7.0**

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Электротехника, электроника, системы автоматизации / Электроустановки, электромонтажные материалы / Модульные последовательные встраиваемые приборы для распределительных шкафов / Встраиваемые выключатели для распределительных устройств (ecf@ss10.0.1-27-14-23-01 [AFZ813014])			
Switching function			Control switch
Number of contacts as normally open contact			3
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Number of poles			3
Rated current		A	16
Rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	0.025
Short-circuit breaking capacity (Icw)		kA	10
Voltage type			AC
Forced segregation (according to DIN VDE 0113)			No
With signal lamp			No
Colour calotte			Other
Lamp type			Other
Lamp socket			Other
Max. lamp power		W	0
Width in number of modular spacings			1
Built-in depth		mm	80
Degree of protection (IP)			IP40