



Предохранитель, 80 А, AC 7.2 kV, 40 кА, 3", 76 x 292 mm, резерв, DIN, с наклейкой

Тип **7.2KV 80Amp 3" 'J' DIN Fuse**
 Каталог № **7.2TFLSJ80**

Abbildung ähnlich

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Номинальный ток	I	A	80
Номинальное напряжение			AC 7.2 kV
Типоразмер			3"
Типоразмер			76 x 292 mm
Категория применения			резерв
Индикатор состояния			с наклейкой
Отключающая способность		кА	40
возможно использование для типоразмеров/оборудования			защита трансформаторов для использования внутри и вне помещений
Стандарт/сертификат			DIN
Стандарты/предписания			DIN 43625 VDE 0670-4 VDE 0670-402 IEC 60282-1

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	80
Rated voltage		kV	7.2
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	40
Utilization category			Other
Application			Primary side transformer protection
Length		mm	292
Diameter		mm	76
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			DIN
Release characteristic			Other
Installation technique			Air