



Предохранитель VT, среднее напряжение, 3.15 А, AC 7.2 kV, 45 кА, BS88, 25.4 x 195 mm, резерв, BS, IEC

Тип **7.2KV 3.15A FUSE**
Каталог № **7.2ABCN223.15**

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель VT
Область применения			среднее напряжение
Номинальный ток	I	A	3.15
Номинальное напряжение			AC 7.2 kV
Типоразмер			BS88
Типоразмер			25.4 x 195 mm
Категория применения			резерв
Отключающая способность		кА	45
возможно использование для типоразмеров/оборудования			трансформаторы напряжения и вспомогательные трансформаторы
Стандарт/сертификат			BS IEC
Форма			цилиндрический с одним концом со шпилькой
Стандарты/предписания			BS2692-1 IEC 60282-1

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	3.15
Rated voltage		kV	7.2
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	45
Utilization category			Other
Application			Auxiliary transformer protection
Length		mm	254
Diameter		mm	25.4
Performance category according to IEC 60282-1			Back-up
With striker			No
Standard			IEC
Release characteristic			Other
Installation technique			Air