



Дверной выключатель

Тип **NWS-TKT**  
Каталог № **255420**

**Программа поставок**

|                |  |                                    |
|----------------|--|------------------------------------|
| Принадлежности |  | Освещение распределительного шкафа |
| Описание       |  | Дверной контактный выключатель     |
| Описание       |  | Дверной контактный выключатель     |
| Описание       |  | Дверной контакт                    |

**Технические характеристики согласно ETIM 7.0**

|  |    |                      |
|--|----|----------------------|
| Sensors (EG000026) / End switch (EC000030)   |    |                      |
| Электротехника, электроника, системы автоматизации / Сенсорная техника, датчики / Position switch / Position switch (Type 1) (ec@ss10.0.1-27-27-06-01 [AGZ382015]) |    |                      |
| Width sensor   | mm | 30                   |
| Diameter sensor  | mm | 8.2                  |
| Height of sensor   | mm | 74                   |
| Length of sensor   | mm | 76                   |
| Rated operation current Ie at AC-15, 24 V  | A  | 6                    |
| Rated operation current Ie at AC-15, 125 V   | A  | 6                    |
| Rated operation current Ie at AC-15, 230 V   | A  | 6                    |
| Rated operation current Ie at DC-13, 24 V  | A  | 3                    |
| Rated operation current Ie at DC-13, 125 V   | A  | 0.3                  |
| Rated operation current Ie at DC-13, 230 V   | A  | 0.8                  |
| Switching function   |    | Quick-break switch   |
| Switching function latching  |    | No                   |
| Output electronic  |    | No                   |
| Forced opening   |    | No                   |
| Number of safety auxiliary contacts  |    | 2                    |
| Number of contacts as normally closed contact  |    | 1                    |
| Number of contacts as normally open contact  |    | 1                    |
| Number of contacts as change-over contact  |    | 0                    |
| Type of interface  |    | None                 |
| Type of interface for safety communication   |    | None                 |
| Construction type housing  |    | Other                |
| Material housing   |    | Plastic              |
| Coating housing  |    | Other                |
| Type of control element  |    | Plunger              |
| Alignment of the control element   |    | Other                |
| Type of electric connection  |    | Cable entry metrical |
| With status indication   |    | No                   |
| Suitable for safety functions  |    | No                   |
| Explosion safety category for gas  |    | None                 |
| Explosion safety category for dust   |    | None                 |
| Ambient temperature during operating   | °C | -25 - 70             |
| Degree of protection (IP)  |    | IP65                 |
| Degree of protection (NEMA)  |    |                      |