## ТЕХНИЧЕСКИЙ ПАСПОРТ - NWS-TKT



## Дверной выключатель



Тип NWS-ТКТ Каталог № 255420

## Программа поставок

| Принадлежности | Освещение распределительного шкафа |
|----------------|------------------------------------|
| Описание       | Дверной контактный выключатель     |
| Описание       | Дверной контактный выключатель     |
| Описание       | Дверной контакт                    |

## **Технические характеристики согласно ЕТІМ 7.0**

| Технические характеристики согласно ETIM 7.0  |   |    |                      |  |
|---|---|----|----------------------|--|
| Sensors (EG000026) / End switch (EC000030)  |   |    |                      |  |
| Электротехника, электроника, системы автоматизации / Сенсорная техника, датчики / Position switch / Position switch (Type 1) (ecl@ss10.0.1-27-27-06-01 [AGZ382015]) |   |    |                      |  |
| Width sensor  | ı | mm | 30                   |  |
| Diameter sensor   | ı | mm | 8.2                  |  |
| Height of sensor  | ı | mm | 74                   |  |
| Length of sensor  | ı | mm | 76                   |  |
| Rated operation current le at AC-15, 24 V   |   | Α  | 6                    |  |
| Rated operation current le at AC-15, 125 V  |   | A  | 6                    |  |
| Rated operation current le at AC-15, 230 V  |   | А  | 6                    |  |
| Rated operation current le at DC-13, 24 V   |   | A  | 3                    |  |
| Rated operation current le  at DC-13, 125 V   |   | A  | 0.3                  |  |
| Rated operation current le  at DC-13, 230 V   | , | A  | 0.8                  |  |
| Switching function  |   |    | Quick-break switch   |  |
| Switching function latching   |   |    | No                   |  |
| Output electronic   |   |    | No                   |  |
| Forced opening  |   |    | No                   |  |
| Number of safety auxiliary contacts   |   |    | 2                    |  |
| Number of contacts as normally closed contact   |   |    | 1                    |  |
| Number of contacts as normally open contact   |   |    | 1                    |  |
| Number of contacts as change-over contact   |   |    | 0                    |  |
| Type of interface   |   |    | None                 |  |
| Type of interface for safety communication  |   |    | None                 |  |
| Construction type housing   |   |    | Other                |  |
| Material housing  |   |    | Plastic              |  |
| Coating housing   |   |    | Other                |  |
| Type of control element   |   |    | Plunger              |  |
| Alignment of the control element  |   |    | Other                |  |
| Type of electric connection   |   |    | Cable entry metrical |  |
| With status indication  |   |    | No                   |  |
| Suitable for safety functions   |   |    | No                   |  |
| Explosion safety category for gas   |   |    | None                 |  |
| Explosion safety category for dust  |   |    | None                 |  |
| Ambient temperature during operating  |   | °C | -25 - 70             |  |
| Degree of protection (IP)   |   |    | IP65                 |  |
| Degree of protection (NEMA)   |   |    |                      |  |