



Выключатель нагрузки, 1П, 40А

Тип **ZP-A40/1**
Каталог № **248263**

Технические характеристики согласно ETIM 7.0

| | | | |
|--|--|----|------------|
| Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545) | | | |
| Электротехника, электроника, системы автоматизации / Электроустановки, электромонтажные материалы / Модульные последовательные встраиваемые приборы для распределительных шкафов / Встраиваемые выключатели для распределительных устройств (ecl@ss10.0.1-27-14-23-01 [AFZ813014]) | | | |
| Switching function | | | Off switch |
| Number of contacts as normally open contact | | | 1 |
| Number of contacts as normally closed contact | | | 1 |
| Number of contacts as change-over contact | | | 0 |
| Number of poles | | | 1 |
| Rated current | | A | 40 |
| Rated voltage | | V | 400 |
| Min. rated voltage | | V | 230 |
| Rated switching capacity | | kA | 0 |
| Short-circuit breaking capacity (Icw) | | kA | 3 |
| Voltage type | | | AC |
| Forced segregation (according to DIN VDE 0113) | | | No |
| With signal lamp | | | No |
| Colour calotte | | | |
| Lamp type | | | |
| Lamp socket | | | |
| Max. lamp power | | W | 0 |
| Width in number of modular spacings | | | 1 |
| Built-in depth | | mm | 60 |
| Degree of protection (IP) | | | IP40 |