



Приоритетное реле, 8А

Тип **Z-LAR8-0**  
Каталог № **248256**

### Технические характеристики согласно ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Load shedding relay for distribution board (EC001655)		
Электротехника, электроника, системы автоматизации / Электроустановки, электромонтажные материалы / Модульные последовательные встраиваемые приборы для распределительных шкафов / Load shedding relay for distribution board (ecl@ss10.0.1-27-14-23-32 [ACN383011])		
Rated voltage	V	250
Rated current Iu	A	3 - 8
Just-operate current	A	3 - 8
Max. time-delayed switch-off	ms	0
Max. continuous current	A	10
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Rated current (control contacts)	A	1
Max. switching voltage (control contacts)	V	250
Max. switching power (control contacts)	VA	7.7
Electrical lifespan (control contacts)	c (contacts)	100000
Mechanical lifetime (control contacts)	c (contacts)	0
Max. electrical switching cycles	c/h	3600
Voltage type		AC
Mounting method		DIN rail
Width in number of modular spacings		1
Built-in depth	mm	60
Degree of protection (IP)		IP20