



Предохранитель VT, среднее напряжение, 3 А, AC 12 kV, 1", 203 x 25.4 мм, резерв, BS, IEC, ESI, маслонепроницаемый

Тип **12KV 3AMP 1" VT FUSE**  
Каталог № **120MDNN3**

Abbildung ähnlich

## Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель VT
Область применения			среднее напряжение
Номинальный ток	I	A	3
Номинальное напряжение			AC 12 kV
Типоразмер			1"
Типоразмер			203 x 25.4 mm
Категория применения			резерв
Описание			маслонепроницаемый
возможно использование для типоразмеров/оборудования			трансформаторы напряжения и вспомогательные трансформаторы
Стандарт/сертификат			BS IEC ESI
Форма			цилиндрический
Стандарты/предписания			BS2692-1 IEC 60282-1 ESI 12-8

## Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	3
Rated voltage		kV	12
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	40
Utilization category			Other
Application			Auxiliary transformer protection
Length		mm	203
Diameter		mm	25.4
Performance category according to IEC 60282-1			Back-up
With striker			No
Standard			British Standard
Release characteristic			Other
Installation technique			Oil