



**Предохранитель двигателя, 100 А, AC 3.6 kV, 50 кА, 51 x 275 mm, резерв, BS, с наклейкой**

**Тип** 3.6KV 80Amp 2" MOTORSTART FUSE  
**Каталог №** 3.6WDOH7100

Abbildung ähnlich

## Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель двигателя
Номинальный ток	I	A	100
Номинальное напряжение			AC 3.6 kV
Типоразмер			51 x 275 mm
Категория применения			резерв
Индикатор состояния			с наклейкой
Отключающая способность		кА	50
возможно использование для типоразмеров/оборудования			защита двигателя
Стандарт/сертификат			BS
Форма			цилиндрический со смещенными винтовыми наконечниками
Стандарты/предписания			BS2692-1

## Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	80
Rated voltage		kV	3.6
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		кА	50
Utilization category			Other
Application			Motor protection
Length		mm	254
Diameter		mm	51
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			British Standard
Release characteristic			Other
Installation technique			Air