



Предохранитель, среднее напряжение, 31.5 А, AC 24 kV, 35.5 кА, 2", 51 x 565 mm, полный диапазон, BS, с наклейкой

Тип 24KV 31.5Amp 2" FULL RANGE FUSE
Каталог № 24FDIHA31.5

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Область применения			среднее напряжение
Номинальный ток	I	A	31.5
Номинальное напряжение			AC 24 kV
Типоразмер			2"
Типоразмер			51 x 565 mm
Категория применения			полный диапазон
Индикатор состояния			с наклейкой
Отключающая способность		кА	35.5
возможно использование для типоразмеров/оборудования			Защита трансформаторов
Стандарт/сертификат			BS
Форма			цилиндрический
Стандарты/предписания			BS2692-1

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	31.5
Rated voltage		kV	24
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	35.5
Utilization category			Other
Application			Primary side transformer protection
Length		mm	565
Diameter		mm	51
Performance category according to IEC 60282-1			Full-range
With striker			Yes
Standard			British Standard
Release characteristic			Other
Installation technique			Air