



Держатель/разъединитель, 400А, размер 2

Тип PIFT2H311C405MM
Каталог № 161054
Alternate Catalog No. PIFT2H311C405MM

Технические характеристики согласно ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)		
Электротехника, электроника, системы автоматизации / Низковольтная коммутационная техника / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss10.0.1-27-37-14-01 [AKF058013])		
Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	690
Rated permanent current Iu	A	400
Rated operation power at AC-23, 400 V	kW	0
Conditioned rated short-circuit current Iq	kA	80
Rated short-time withstand current Icw	kA	0
Suitable for fuses		NH2
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Side
Equipped with connectors		Yes
Suitable for ground mounting		No
Suitable for front mounting 4-hole		No
Suitable for busbar mounting		Yes
Type of control element		Cover grip
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP40

Дополнительная информация о продуктах (ссылки)

Листок-вкладыш с инструкцией для PIFT	https://es-assets.eaton.com/ENGINEERING/CONFIGURATOR/XENERGY/IL-PIFT-01M-2018-08.pdf
---------------------------------------	---