DATASHEET - KLV-4UPP-4PR



For indoors, flush-mounting, 4-row; form of delivery for projects

Powering Business Worldwide*

Part no. KLV-4UPP-4PR Catalog No. 178869

Delivery program

Delivery program			
Product image			
Basic function			Basic device
Product function			Installation distribution boards
Product range			KLV for projects
Design			Flush mounted
Installation site			Indoor
Type of installation			Flush mounting
Door/Flap			White
Degree of Protection			IP30
Colour			White
Module rack			Rail-frame
Shroud for protection against accidental contact			Plastic
Rows	Count		4
Module units per row			12
Description			IP30 Protection Class II Plastic housing
PE and N terminals design			Plug-in terminals
PE and N terminals	Number x cross- sectional area	mm ²	PE: 4 x (2.5 - 25) + 28 x (0.5 - 4) N: 4 x (2.5 - 25) + 28 x (0.5 - 4)
Equipment supplied			Device support rails Front cover Neutral-/protective conductor terminal Cable retainer Installation instructions Imprintable sheet

Technical data

General

Standards			IEC/EN 62208, IEC/EN 60670-24 (PD)	
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform	
Ambient temperature		°C	-5 - +40	
Degree of Protection			IP30	
Protection class			II (totally insulated)	
Rated operational voltage	Ue	V AC	400	
Rated frequency	f	Hz	50	
Material characteristics				
Material			Polystyren (plastic)	
Colour			white (RAL 9016)	
Material properties				
Mechanical				
Impact resistance			IK05	

Technical data ETIM 7.0

Distribution boards (EG000023) / Accessories for small distribution board (EC002287)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Electrical distribution system (incl. small distribution board, accessories) (ecl@ss10.0.1-27-14-24-92 [AFR782003])

Type of accessory Other

Additional product information (links)

Product overview (Web) http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm