



Маслонаполненный предохранитель, среднее напряжение, 125 А, АС 12 кV, 40 кА, 2.5", 359 x 63.5 мм, резерв, BS, IEC, ESI, с наклейкой, маслoneпроницаемый

Тип 12KV 125A 2.5" OIL FUSE
Каталог № 120LGMA125

Программа поставок

Программа поставок			Предохранитель
Основная функция			Маслонаполненный предохранитель
Область применения			среднее напряжение
Номинальный ток	I	A	125
Номинальное напряжение			AC 12 kV
Типоразмер			2.5"
Типоразмер			359 x 63.5 mm
Категория применения			резерв
Индикатор состояния			с наклейкой
Описание			маслoneпроницаемый
Отключающая способность		кА	40
возможно использование для типоразмеров/оборудования			защита первичной обмотки трансформатора и маслонаполненная комбинированная сборка выключателя с предохранителем
Стандарт/сертификат			BS IEC ESI
Форма			цилиндрический
Стандарты/предписания			BS2692-1 IEC 60282-1 ESI 12-8

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	125
Rated voltage		kV	12
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	40
Utilization category			Other
Application			Primary side transformer protection
Length		mm	359
Diameter		mm	63.5
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			British Standard
Release characteristic			Other
Installation technique			Oil