



Предохранитель, среднее напряжение, 100 А, AC 24 kV, 63 кА, 3", 76 x 442 mm, резерв, DIN, с наклейкой



Powering Business Worldwide™

Тип **24KV 100Amp 3" 'J' DIN Fuse**
Каталог № **24TFMEJ100**

Abbildung ähnlich

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Область применения			среднее напряжение
Номинальный ток	I	A	100
Номинальное напряжение			AC 24 kV
Типоразмер			3"
Типоразмер			76 x 442 mm
Категория применения			резерв
Индикатор состояния			с наклейкой
Отключающая способность		кА	63
возможно использование для типоразмеров/оборудования			защита трансформаторов для использования внутри и вне помещений
Стандарт/сертификат			DIN
Стандарты/предписания			DIN 43625 VDE 0670-4 IEC 60282-1

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	100
Rated voltage		kV	24
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	63
Utilization category			Other
Application			Primary side transformer protection
Length		mm	442
Diameter		mm	76
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			DIN
Release characteristic			Other
Installation technique			Air