

ТЕХНИЧЕСКИЙ ПАСПОРТ - 3.6KV 40AMP 2" 'J' DIN FUSE ADO



Предохранитель, среднее напряжение, 40 А, AC 3.6 kV, 40 кА, 2", 51 x 192 мм, резерв, DIN, с наклейкой



Тип **3.6KV 40Amp 2" 'J' DIN Fuse ADO**
Каталог № **3.6ADOSJ40**

Abbildung ähnlich

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Область применения			среднее напряжение
Номинальный ток	I	A	40
Номинальное напряжение			AC 3.6 kV
Типоразмер			2"
Типоразмер			51 x 192 mm
Категория применения			резерв
Индикатор состояния			с наклейкой
Отключающая способность		кА	40
возможно использование для типоразмеров/оборудования			защита трансформаторов для использования внутри помещений
Стандарт/сертификат			DIN
Стандарты/предписания			DIN 43625 VDE 0670-4 IEC 60282-1

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	40
Rated voltage		kV	3.6
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	40
Utilization category			Other
Application			Primary side transformer protection
Length		mm	254
Diameter		mm	51
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			DIN
Release characteristic			Other
Installation technique			Air