



Предохранитель, среднее напряжение, 10 А, AC 17.5 kV, 35.5 кА, 2", 51 x 292 мм, резерв, DIN, с наклейкой



Powering Business Worldwide™

Тип **17.5KV 10AMP 2" DIN FUSE**
Каталог № **17.5TDLSJ10**

Abbildung ähnlich

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Область применения			среднее напряжение
Номинальный ток	I	A	10
Номинальное напряжение			AC 17.5 kV
Типоразмер			2"
Типоразмер			51 x 292 mm
Категория применения			резерв
Индикатор состояния			с наклейкой
Отключающая способность		кА	35.5
возможно использование для типоразмеров/оборудования			защита трансформаторов для использования внутри помещений
Стандарт/сертификат			DIN
Стандарты/предписания			DIN 43625 VDE 0670-4 VDE 0670-402 IEC 60282-1

Технические характеристики согласно ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	10
Rated voltage		kV	17.5
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	35.5
Utilization category			Other
Application			Primary side transformer protection
Length		mm	292
Diameter		mm	51
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			DIN
Release characteristic			Other
Installation technique			Air