



**Outdoors flush-mounting/hollow-wall model with the requested RAL color; form of delivery for projects**

**Part no. KLV-F3L-4PR-RAL\***  
**Catalog No. 178894**

## Delivery program

Product image			
Basic function			Basic device
Product function			Installation distribution boards
Product range			KLV for projects
Design			Hollow wall Flush mounted
Installation site			Indoor
Type of installation			Hollow-wall mounting and flush mounting
Door/Flap			Desired color
Degree of Protection			IP30
Colour			Desired color
Shroud for protection against accidental contact			Plastic
Rows	Count		3
Module units per row			12
Description			IP30 Protection Class II Sheet steel door, desired color (RAL)
Equipment supplied			Door frame with door 3D adjustment element for mounting Installation instructions

## Technical data

### General

Standards			IEC/EN 62208, IEC/EN 60670-24
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform
Ambient temperature		°C	-5 - +40
Degree of Protection			IP30
Protection class			II (totally insulated)
Rated frequency	f	Hz	50

### Material characteristics

Material			Sheet steel, powder-coated
Colour			Desired color (RAL)

### Material properties

Mechanical			
Impact resistance			IK05

## Technical data ETIM 7.0

Distribution boards (EG000023) / Accessories for small distribution board (EC002287)			
Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Electrical distribution system (incl. small distribution board, accessories) (ec@ss10.0.1-27-14-24-92 [AFR782003])			
Type of accessory			Other

## Additional product information (links)

Product overview (Web)	<a href="http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm">http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm</a>
------------------------	---

