



Вставка для ограничителя перенапряжения, класс D



Тип SPDT3-335
Каталог № 170486
Alternate Catalog No. SPDT3-335

Программа поставок

Продукты		Устройство защиты от скачков напряжения (сетевой фильтр)
Область применения		Жилые здания Коммерческие здания Открытое пространство

Технические характеристики согласно ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)			
Электротехника, электроника, системы автоматизации / Защитные устройства и аппараты / Разрядники защиты от перенапряжения / Surge protection device for power supply systems (ec1@ss10.0.1-27-13-08-05 [ACN278011])			
System configuration DC			No
System configuration IT			No
System configuration TN			No
System configuration TN-C			No
System configuration TN-C-S			No
System configuration TN-S			No
System configuration TT			No
System configuration other			Yes
Number of conductors (without earthing)			0
Nominal discharge surge current (8/20)		kA	2.5
Nominal voltage AC		V	335
Nominal voltage DC		V	0
Short-circuit breaking capacity (Iscbr)		kA	0
Max. continuous voltage AC		V	335
Max. discharge surge current (8/20)		kA	10
Max. continuous voltage DC		V	0
Mounting method			On basic element
Construction size			1 modular spacing
Max. PV-voltage		V	0
Voltage protection level		kV	1.6
Max. conductor cross section solid (solid, stranded)		mm ²	25
Max. conductor cross section flexible (fine-strand)		mm ²	0
Voltage protection level L-N		kV	0
Voltage protection level N-PE		kV	0
With remote signalling contact			No
Integrated backup fuse			No
Signalling at the device			Optic
Category type 2			No
Degree of protection (IP)			IP20