



Приоритетное реле, 8А

Тип Z-LAR8-S
Каталог № 248259

Abbildung ähnlich

Технические характеристики согласно ETIM 7.0

| Devices for distribution board-/surface mounting (EG000062) / Load shedding relay for distribution board (EC001655) | | |
|--|--------------|----------|
| Электротехника, электроника, системы автоматизации / Электроустановки, электромонтажные материалы / Модульные последовательные встраиваемые приборы для распределительных шкафов / Load shedding relay for distribution board (ec1@ss10.0.1-27-14-23-32 [ACN383011]) | | |
| Rated voltage | V | 250 |
| Rated current Iu | A | 3 - 8 |
| Just-operate current | A | 3 - 8 |
| Max. time-delayed switch-off | ms | 0 |
| Max. continuous current | A | 10 |
| Number of contacts as normally open contact | | 1 |
| Number of contacts as normally closed contact | | 0 |
| Number of contacts as change-over contact | | 0 |
| Rated current (control contacts) | A | 1 |
| Max. switching voltage (control contacts) | V | 250 |
| Max. switching power (control contacts) | VA | 7.7 |
| Electrical lifespan (control contacts) | c (contacts) | 100000 |
| Mechanical lifetime (control contacts) | c (contacts) | 0 |
| Max. electrical switching cycles | c/h | 3600 |
| Voltage type | | AC |
| Mounting method | | DIN rail |
| Width in number of modular spacings | | 1 |
| Built-in depth | mm | 60 |
| Degree of protection (IP) | | IP20 |