



Hollow wall compact distribution board; multimedia; 3-rows; flush sheet steel door



Powering Business Worldwide™

Part no. KLV-36HWM-F
Catalog No. 178834

Delivery program

Product image			
Basic function			Basic device
Product function			Installation distribution boards
Product range			KLV multimedia
Design			Hollow wall
Installation site			Indoor
Type of installation			Hollow-wall mounting
Door/Flap			White
Degree of Protection			IP30
Colour			White
Module rack			Media mounting plate
Shroud for protection against accidental contact			Without
Rows	Count		3
Module units per row			12
Description			IP30 Protection Class II Plastic enclosure with sheet steel door, white (RAL 9016) Note: To obtain protection class II, all devices installed on the mounting plate must be of the fully insulated type.
Cable entries			Cable entries on top and bottom, side, back plate
PE and N terminals design			Without
Equipment supplied			Wall trough Door/Frame Device support rails Microperforated mounting plate Device holder 2x single-way socket outlet Spirit level for leveling 3D adjustment element for mounting designed to adjust the mounting depth by up to 18 mm Cable retainer Hollow-wall anchor Installation instructions

Technical data

General			
Standards			IEC/EN 62208, IEC/EN 60670-24 (GP)
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform
Ambient temperature		°C	-5 - +40
Degree of Protection			IP30
Protection class			II (totally insulated)
Rated operational voltage	Ue	V AC	230
Rated frequency	f	Hz	50

Material characteristics

Material			Polystyren (plastic) Sheet steel, powder-coated
Colour			white (RAL 9016)

Material properties

Mechanical			
------------	--	--	--

Impact resistance				IK05
-------------------	--	--	--	------


Design verification as per IEC/EN 61439


Technical data for design verification				
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890				
Individual enclosure, flush mounting	P _V	W		20
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890				
Individual enclosure, flush mounting	P _V	W		43
IEC/EN 61439 design verification				
10.2 Strength of materials and parts				
10.2.2 Corrosion resistance				Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures				Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat				Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects				850 °C; meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation				Not relevant to indoor installations.
10.2.5 Lifting				Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact				IK05
10.2.7 Inscriptions				Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES				IP30
10.4 Clearances and creepage distances				Is the panel builder's responsibility.
10.5 Protection against electric shock				Protection class 2, therefore not applicable.
10.6 Incorporation of switching devices and components				Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections				Is the panel builder's responsibility.
10.8 Connections for external conductors				Is the panel builder's responsibility.
10.9 Insulation properties				
10.9.2 Power-frequency electric strength				U _i = 400 V AC
10.9.3 Impulse withstand voltage				4 kV
10.9.4 Testing of enclosures made of insulating material				Meets the product standard's requirements.
10.10 Temperature rise				The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating				Is the panel builder's responsibility.
10.12 Electromagnetic compatibility				Is the panel builder's responsibility.
10.13 Mechanical function				Meets the product standard's requirements.

Technical data ETIM 7.0

Data and telecommunication (EG000037) / Distributor for telecommunication (EC000374)				
Electric engineering, automation, process control engineering / Electrical installation, device / Connection devices / Distributor for telecommunication (ecl@ss10.0.1-27-14-44-26 [AEI678006])				
Model				Distributor enclosure
Mounting method				Flush mounted (plaster)
With connecting lugs				No
Max. number of dual cores				12
Mounting dimension (standardised)				Other
DIN-compatible				Yes
110-compatible				Yes
LSA				No
SID				No
Material				Steel plate/plastic
Degree of protection (IP)				IP30
Degree of protection (NEMA)				Other
Colour				White
Height		mm		590
Width		mm		360
Depth		mm		100
Number of mountable connection strips				0

Dimensions





Additional product information (links)

Product overview (Web)

<http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm>